



MANUFACTURERS
"AFC" LOGO
.025 MAX
RAISED OR INDENTED



"X" ALLOY STEEL
GRADE MARK



SCALE: 1.5X

DESIGN NOTES: AN3-24A AIRFRAME BOLT

1. LENGTH 2-17/32" (2.531"), GRIP 2-1/8" (2.125"), THREAD 10-32 UNF-3A.
2. PROCUREMENT SPECIFICATION NASM6812.
3. PREFERRED MATERIAL ALLOY STEEL PER PROCUREMENT SPECIFICATION.
UNS G40370 AMS6300 DFAR EXEMPT
UNS G87400 AMS6322 DFAR APPLIES
UNS G41400 AMS6382 DFAR APPLIES
UNS G41300 AMS-S-6758 DFAR APPLIES
4. HEAT TREAT AMS-2759 HRC 26-32.
5. FINISH CADMIUM PLATED PER AMS-QQ-P-416, TYPE 2 (YELLOW), CLASS 2.
6. THREADS 10-32 UNF-3A ROLLED PROCESS PER MIL-S-7742.
7. TENSILE 2,210 LBS. [9,830 N] MIN.
8. YIELD 1,690 LBS. [7,517 N] MIN.
9. SINGLE SHEAR 2,125 LBS. [9,415 N] MIN. SHORT LENGTH N/A.

EXAMPLE PART NUMBER

AFC 3-24 C2 CADMIUM TYPE 2 YELLOW PLATING
AFC 3-24 C1 CADMIUM TYPE 1 PLAIN WHITE PLATING
AFC 3-24 TDC THERMAL DIFFUSION COATED ASTM A1059
↑ FINISH
↑ LENGTH 2.531"
↑ BODY SIZE & THREAD .190-32 UNF-3A
↑ MANUFACTURER AIRFASCO



ACTUAL SIZE

UNCONTROLLED

CONFORMS TO: NASM3 THRU NASM20
PART NUMBER: AN3-24A

DIMENSIONS ARE IN INCHES AND TOLERANCES ARE AS SHOWN BELOW. DIMENSIONAL TOLERANCES AND SYMBOLS PER ANSI Y14.5M-1982

PROPRIETARY PARTS SHOWN IN THIS DRAWING ARE THE SUBJECT OF ISSUED UNITED STATES AND FOREIGN PATENTS AND PATENTS PENDING. UNAUTHORIZED REPRODUCTION AND/OR DISTRIBUTION OF THIS DRAWING IS STRICTLY PROHIBITED.

AIRFASCO.com

2655 HARRISON AVE SW, CANTON, OHIO 44706 USA

APPROVALS		DATE	PART NUMBER: AN3-24A_AFC3-24C2		REV
ANGLES	±5°	DRAWN C.D.	6/10/13		
XX	±.03"	CHECKED T.W.	6/10/13		
XXX	±.010"	ENG APPR B.E.	6/10/13		
XXXX	±.001"	MGR APPR D.D.	6/10/13		
SCALE: 1.5X		DRAWING NUMBER: AN3-24A_AFC3-24C2		SHEET 1 OF 1	

SIZE A	MATERIAL: 4037 / 8740 OR AS NOTED	EST. WEIGHT: .023 / EACH LBS. [10.5 g]
--------	-----------------------------------	--